



NOTES:

1. DIMENSIONS IN MILLIMETERS
2. LEAK TIGHT TO 1X10E-9 ATM cc/sec He
3. NICKEL PLATED PINS 150 μm MIN THICK PER QQ-N-290, CLASS1
4. VOLTAGE RATING: 2.0KV DC
5. CURRENT RATING: 5 AMPS/PIN
6. TEMPERATURE RANGE: -269 °C TO 450 °C (BAKEOUT)
7. BCE TO CLEAN PART PER SPEC 010-810018 TYPE 1 PART
8. INDIVIDUALLY PACKED IN PLASTIC BAG WITH LABEL USING INDELIBLE INK SHOWING PART NUMBER, SUPPLIER ID, AND DATE CODE

The information given herein is based on data believed to be accurate, but BCE makes no expressed or implied warranties as to its accuracy and assumes no liability arising out of its use by others. This information does not constitute a license to use or infringe on any patents

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF BELLOVE CO. ENGINEERS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF BELLOVE CO. ENGINEERS IS PROHIBITED.

UNLESS OTHERWISE SPECIFIED:	
DIMENSIONS ARE IN MM	
TOLERANCES:	
FRACTIONAL ±	
ANGULAR: MACH ±	BEND ±
TWO PLACE DECIMAL ±.254	
THREE PLACE DECIMAL ±.127	
INTERPRET GEOMETRIC TOLERANCING PER:	
MATERIAL	SEE DWG
FINISH	N/A
DO NOT SCALE DRAWING	

BCE		P/N: TBD	
TITLE:			
9Pin 48mm FEEDTHROUGH FLANGE			
SIZE	DWG. NO.	REV	
A	BCE10833	-	
SCALE: NTS	WEIGHT: N/A	SHEET 1 OF 1	