



**NOTES**

1. 24VOLT, 50WATT.
2. 200 C MAX TEMP @ 1.5" SECTION
3. HERMETICALLY SEALED BCE, BLACK EPOXY P/N: MHC2553
4. 300 SERIES STAINLESS STEEL,

The information given herein is based on data believed to be accurate, but BCE makes no expressed or implied warranties as to its accuracy and assumes no liability arising out of its use by others. This information does not constitute a license to use or infringe on any patents

**PROPRIETARY AND CONFIDENTIAL**  
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF BELLOVE CO. ENGINEERS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF BELLOVE CO. ENGINEERS IS PROHIBITED.

UNLESS OTHERWISE SPECIFIED:	
DIMENSIONS ARE IN INCHES	
TOLERANCES:	
FRACTIONAL ±	
ANGULAR: MACH ± BEND ±	
TWO PLACE DECIMAL ± .010	
THREE PLACE DECIMAL ± .005	
INTERPRET GEOMETRIC TOLERANCING PER:	
MATERIAL	SEE DWG
FINISH	N/A
DO NOT SCALE DRAWING	



TITLE:		
HEM SEALED HEATER		
SIZE	DWG. NO.	REV
<b>A</b>	BCE10800	-
SCALE: NTS	WEIGHT: N/A	SHEET 1 OF 1