



NOTES:

- 1) ELECTRICAL: 30KW (+/-10%), 480 VOLTS 3-PHASE WITH TERMINAL BLOCK, MUST PASS 700VDC, HI-POT AT 0.5ma CURRENT LEAKAGE FOR 5 SECONDS PRIOR TO SHIPMENT.
- 2) 0.25" DIAMTER TYPE "K" SENSOR LOCATED AT OUTLET END, WELDED TO PIPE.
- 3) PART TESTED TO 80 PSI AT 20-25C
- 4) 700C MAX OPERATING TEMPERATURE AT OUTLET

<p>The information given herein is based on data believed to be accurate, but BCE makes no expressed or implied warranties as to its accuracy and assumes no liability arising out of its use by others. This information does not constitute a license to use or infringe on any patents</p>	UNLESS OTHERWISE SPECIFIED:		PART. NO.	
	DIMENSIONS ARE IN INCHES			
	TOLERANCES:			
	FRACTIONAL ± ANGULAR: MACH ± BEND ± TWO PLACE DECIMAL ±.005 THREE PLACE DECIMAL ±.001			
<p>PROPRIETARY AND CONFIDENTIAL</p> <p>THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF BELLOVE CO. ENGINEERS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF BELLOVE CO. ENGINEERS IS PROHIBITED.</p>	INTERPRET GEOMETRIC TOLERANCING PER:		TITLE: <h2 style="margin: 0;">Mega Clean Flow Heater -</h2>	
	MATERIAL			
	SEE DWG		SIZE	DWG. NO.
FINISH		A	BCE11254	-
DO NOT SCALE DRAWING		SCALE: NTS		WEIGHT: N/A
				SHEET 1 OF 1